




BBF144/..

- high load-bearing capacity
- replaceable expansion insert
- with loose/fixed flange



FEATURES

watertight, resistant to heavy loads, trafficable by fork-lift trucks, expansion insert can be replaced in the event of damage without damaging the adjacent covering, abrasion-, weather- and temperature-resistant (-40°C to +120°C), resistant to de-icing salt and waste water (alkalis, microbes, bacteria)

APPLICATIONS

parking decks, parking garages, underground garages, ramp crossings, pedestrian bridges, all industrial applications

MATERIAL

hot-dip galvanised steel, (stainless steel on request), EPDM expansion insert, joint tape BF20 made of EPDM with lateral bonding flanges made of non-combustible fleece on the top and bottom sides

COVERING TYPES

asphalt, concrete, screed, bitumen welding membrane, liquid plastic

TRAFFICABILITY

passenger cars, trucks, fork-lifts

FORMED PARTS

corner piece, T-piece, cross piece, floor-wall connections, upstand, membrane upstand

NOTES

Specification of profile height (h) from the lower edge of the loose flange.

The joint tape is a product of the BBF ElastoFug joint tape systems. Installation by our own fitters recommended.


TECHNICAL DATA

Movement horizontal:	60 mm (±30 mm)
Movement vertical:	30 mm (±15 mm)
Visible width:	140 mm
Maximal joint width:	100 mm
Load rating:	wheel load 5000 kg up to Ø 150 mm, B = 100 mm
Load rating trucks:	600 kN (DIN 1072)
Load rating forklifts:	150 kN (DIN 1055-3)
Supply length:	3 mtr
Color of expansion insert:	schwarz

DESIGNS

ARTICLE NO.	PROFILE HEIGHT (h)	RECESS (BxT)
BBF144/55	55 mm	370 x 20 mm
BBF144/100	100 mm	370 x 20 mm
BBF144/120	120 mm	370 x 20 mm
BBF144/150	150 mm	370 x 20 mm

Special heights on request.



BBF144

Subject to technical change without notice.