



## VA.8.120/.. GF

- high load-bearing capacity
- replaceable expansion insert
- hygiene-friendly and smooth expansion insert

### FEATURES

watertight, resistant to heavy loads, trafficable by fork-lift trucks, expansion insert can be replaced in the event of damage without damaging the adjacent covering, abrasion-, weather- and temperature-resistant (-40°C to +120°C), resistant to de-icing salt and waste water (alkalis, microbes, bacteria)

### APPLICATIONS

all industrial applications, areas with increased hygiene standards (e.g. kitchens, hospitals etc.)

### MATERIAL

substructure hot-dip galvanised steel and visible surface stainless steel V2A (V4A on request), EPDM expansion insert, Wolfin IB sealing membrane

### COVERING TYPES

asphalt, screed, natural and stone slabs, bitumen welding membrane, liquid plastic, Flüssigkunststoff

### TRAFFICABILITY

passenger cars, trucks, fork-lifts

### FORMED PARTS


corner piece, T-piece, cross piece, floor-wall connections, upstand, membrane upstand

### NOTES

The sealing and expansion insert is flanged with screws M10 at intervals of 150 mm.

The sealing membrane projecting from the joint profile must be integrated into the sealing system to prevent water infiltration from the sides.

Installation by our own fitters recommended.




### TECHNICAL DATA

Movement horizontal:	20 mm (±10 mm)
Movement vertical:	10 mm (±5 mm)
Visible width:	116 mm
Maximal joint width:	50 mm
Load rating:	wheel load 5000 kg up to Ø 150 mm, B = 100 mm
Load rating trucks:	600 kN (DIN 1072)
Load rating forklifts:	150 kN (DIN 1055-3)
Supply length:	3 mtr
Color of expansion insert:	schwarz

### DESIGNS

ARTICLE NO.	PROFILE HEIGHT (h)	RECESS (BxT)
VA.8.120/45 GF	45 mm	1000 x 55 mm
VA.8.120/60 GF	59 mm	1000 x 69 mm
VA.8.120/75 GF	74 mm	1000 x 74 mm
VA.8.120/90 GF	89 mm	1000 x 99 mm
VA.8.120/105 GF	104 mm	1000 x 114 mm
VA.8.120/120 GF	119 mm	1000 x 129 mm
VA.8.120/150 GF	150 mm	1000 x 160 mm

Special heights on request.



Subject to technical change without notice.

# VA.8.120