



VA.8.130/..

- high load-bearing capacity
- flexible to use

FEATURES

watertight, resistant to heavy loads, trafficable by fork-lift trucks, expansion insert can be replaced anytime, abrasion-, weather- and temperature-resistant (-40°C to +120°C), resistant to de-icing salt and waste water (alkalis, microbes, bacteria), a different sealing membrane can be used by arrangement

APPLICATIONS

parking decks, parking garages, underground garages, ramp crossings, pedestrian bridges, all industrial applications

MATERIAL

substructure hot-dip galvanised steel and visible surface stainless steel V2A (V4A on request), EPDM expansion insert, Wolfin IB sealing membrane

COVERING TYPES

coating, concrete, screed, industrial coverings, natural and stone slabs

TRAFFICABILITY

passenger cars, trucks, fork-lifts

FORMED PARTS


upstand, end piece, corner piece, T-piece, cross piece, floor-wall connections

NOTES

The sealing and expansion insert is flanged with screws M10 at intervals of 150 mm.

The sealing membrane projecting from the joint profile must be integrated into the sealing system to prevent water infiltration from the sides.

Installation by our own fitters recommended.




TECHNICAL DATA

Movement horizontal:	60 mm (±30 mm)
Movement vertical:	30 mm (±15 mm)
Visible width:	128 mm
Maximal joint width:	70 mm
Load rating:	wheel load 5000 kg up to Ø 150 mm, B = 100 mm
Load rating trucks:	600 kN (DIN 1072)
Load rating forklifts:	150 kN (DIN 1055-3)
Supply length:	3 mtr
Color of expansion insert:	schwarz

DESIGNS

ARTICLE NO.	PROFILE HEIGHT (h)	RECESS (BxT)
VA.8.130/30	30 mm	340 x 40 mm
VA.8.130/37	37 mm	340 x 47 mm
VA.8.130/45	45 mm	340 x 55 mm
VA.8.130/60	60 mm	340 x 70 mm
VA.8.130/75	75 mm	340 x 85 mm
VA.8.130/90	90 mm	420 x 100 mm
VA.8.130/104	104 mm	420 x 114 mm
VA.8.130/120	120 mm	420 x 130 mm
VA.8.130/150	150 mm	420 x 160 mm
Special heights on request.		



Subject to technical change without notice.

VA.8.130